

# CANYCOM

RIDE-ON BRUSH CUTTER

# CMX2414

A compact, high-output ride-on brush cutter built for tight access, steep ground, and commercial work.

22.4 hp Honda GX690

38.4 in cutting width

25° gradeability

Shaft drive to deck



## BUILT FOR THE JOB

- Hydrostatic main transmission for smooth, controlled ground speed.
- Shaft-driven mower deck with tool-less change swing blades.
- Compact width and tight turning radius for constrained job sites.
- Newly equipped with foldable ROPS, a front brush guard, and 3" more legroom.

Dealer availability and launch timing:

1-888-450-0381

[www.canycomsales.com](http://www.canycomsales.com)

## AT A GLANCE

**948 lb**

MACHINE WEIGHT

**8.7**

mph

TOP SPEED

**6.5 ft**

TURN RADIUS

**1.88**

ACRES/HOUR

**40.2 in**

OVERALL WIDTH

**0-6 in**

CUT HEIGHT

## DIMENSIONS &amp; PERFORMANCE

<b>Operating temperature</b>	5°F to 104°F
<b>Operating altitude</b>	Below approx. 4,920 ft
<b>Machine weight</b>	947.9 lb
<b>Mowing rate</b>	1.88 acres/hr
<b>Overall length</b>	83.8 in
<b>Overall width</b>	40.2 in
<b>Overall height</b>	73.2 in / 40.9 in ROPS folded
<b>Wheelbase</b>	56.2 in
<b>Tread</b>	Front 33.9 in; rear 31.5 in
<b>Ground clearance</b>	5.70 in
<b>High speed range</b>	0–8.7 mph
<b>Low speed range</b>	0–4.8 mph
<b>Minimum turning radius</b>	6.5 ft
<b>Gradeability</b>	25°

## ENGINE, ELECTRICAL, DRIVE &amp; CUTTING

<b>Engine model</b>	Honda GX690
<b>Engine type</b>	Air-cooled 4-cycle V-twin gasoline OHV
<b>Bore × stroke</b>	3.07 × 2.83 in
<b>Displacement</b>	42.0 cu in
<b>Maximum output</b>	22.4 hp @ 3,600 rpm
<b>Maximum torque</b>	Approx. 35.6 lb-ft @ 2,500 rpm
<b>Set engine speed</b>	3,300 rpm
<b>Starter</b>	Electric
<b>Fuel</b>	Automotive unleaded gasoline
<b>Fuel consumption</b>	1.77 US gal/hr noted
<b>Fuel tank capacity</b>	3.7 US gal
<b>Ignition / spark plug</b>	CDI magneto / NGK ZFR5F
<b>Battery</b>	34B17R; 12V / 28Ah
<b>Main transmission</b>	HST, continuously variable
<b>Auxiliary transmission</b>	Constant mesh
<b>Tires</b>	Front 4.00-7 4PR; rear 19×8.00-10 4PR
<b>Steering / brakes</b>	Rack and pinion, round steering wheel / internally expanding brakes
<b>Cutting width</b>	38.4 in
<b>Cutting height</b>	0–6.0 in, stepless
<b>Blade system</b>	2 free knives with stepped stay; shaft drive